INDUSTRIAL OILS

# SARMAX HYDRAULIC OILS VHVI 68.

A very high viscosity index hydraulic oil, built by combining refined mineral base oil with a shear-stable viscosity index improver and a full HVLP additive system.

PRODUCT RANGE
**Hydraulic Oils**

| 68 cSt | 11.5 cSt | 0.867 | 210 °C |
|---|---|---|---|
| Viscosity @ 40°C | Viscosity @ 100°C | Density @ 15 | Flash point |

## APPLICATION

- Excavators, loaders and mobile plant working outdoors
- Systems that must start cold and run hot in the same shift
- Hydrostatic transmissions and travel motors
- Sites replacing a seasonal summer/winter grade change with one fill

**NOT RECOMMENDED**

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| ISO Viscosity @ 40°C | | **68** |
| ISO Viscosity @ 100°C | | **11.5** |
| Density @ 15°C | ASTM D4052 | **0.867** |
| Viscosity Index (Typical) | | **164** |
| Flash Point (COC), °C | | **210** |

Typical values. They do not form a specification.

## PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

## BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 11 industry and OEM approvals, simplifying product consolidation

## PERFORMANCE PROFILE

Suitable where the following specifications are required:

| | |
|---|---|
| **DIN** | 51524 Part 2 and 3 (HVLP) |
| **ISO** | 11158 (HV) |
| **ASTM** | D6158 (HV) |
| **Fives-Cincinnati** | P-68 (ISO 32 – HV), P-69 (ISO 68 – HV), P-70 (ISO 46 – HV) |
| **Parker-Denison** | HF-2, HF-1, HF-0 (HV) (ISO 32, 46, 68) |
| **Sperry-Vickers** | 35 VQ25 |
| **Eaton** | E-FDGN-TB002-EGB 11118.1-2011 (L-HV, L-HS) (ISO 15, 22, 32, 46) |
| **AIST** | 126, 127 (ISO 32, 46, 68) |
| **SEB** | 181222 (ISO 22, 32, 46, 68 and 100) |

## HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS HY0236

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063