INDUSTRIAL OILS

SARMAX HYDROL DETERGENT HYDRAULIC OILS – ISO 46.

A detergent-dispersant hydraulic oil, HLP-D rather than plain HLP.

PRODUCT RANGE
Hydraulic Oils

46 cSt	210 °C	-24 °C
Viscosity @ 40°C	Flash point	Pour point

APPLICATION

- Mobile plant hydraulics exposed to weather
- Marine and dockside systems
- Older equipment with known water ingress
- Combined hydraulic and wet-brake circuits

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51524 Part 2 (HLP-D)
ASTM	D6158 (HM)
ISO	6743-4 (HM)

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
ISO Viscosity @ 40°C		**46**
Pour Point, °C		**-24**
Flash Point (COC), °C		**210**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS HY0301

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063