INDUSTRIAL OILS

# SARMAX ULTRA HYDRAULIC OILS – ISO 32.

The Group II answer to the standard SARMAX hydraulic oil.

PRODUCT RANGE
**Hydraulic Oils**

| 32.6 cSt | 5.7 cSt | 0.8586 |
|---|---|---|
| Viscosity @ 40°C | Viscosity @ 100°C | Density @ 15°C, Kg/L |

## APPLICATION

- Extended-drain hydraulic fills
- Systems on oil analysis programmes
- Hot plant rooms where oxidation life is the limit
- Servo and proportional valve circuits sensitive to varnish

**NOT RECOMMENDED**

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| ISO Viscosity @ 40°C, cSt | | **32.6** |
| ISO Viscosity @ 100°C, cSt | | **5.7** |
| Viscosity Index | ASTM D2270 | **115** |
| Density @ 15°C, Kg/L | | **0.8586** |

Typical values. They do not form a specification.

## PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

## BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 11 industry and OEM approvals, simplifying product consolidation

## PERFORMANCE PROFILE

Suitable where the following specifications are required:

| | |
|---|---|
| **DIN** | 51524 Part 2 (HM, HLP) |
| **ISO** | 11158 (HM) |
| **ASTM** | D6158 (HM) |
| **SAE** | MS1004 (HM) |
| **Parker-Denison** | HF-2, HF-1, HF-0 (ISO 32, 46, 68) |
| **Fives-Cincinnati** | P-68, P-69, P-70 (ISO 32, 68, 46) |
| **Eaton** | E-FDGN-TB002-EGB 11118.1-2011 (L-HL, L-HM) |
| **JCMAS** | P041 HK Hydraulic specification |
| **GM** | LS-2 (ISO 22, 32, 46, 68) |
| **SEB** | 181222 |
| **AIST-US Steel** | 126/127 – R & O Hydraulic Fluids |

## HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS HU0032

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063