INDUSTRIAL OILS

SARMAX ZF HYDRAULIC OILS – ISO 150.

A zinc-free, ashless hydraulic oil on low-sulphur base stocks.

PRODUCT RANGE
Hydraulic Oils

150 cSt	14.3 cSt	0.891	230 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15	Flash point

APPLICATION

- Systems containing bronze, brass or silver-plated parts
- Hydraulics running with persistent water ingress
- Sites minimising heavy metals in their effluent
- Power generation and water industry hydraulics

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
ISO Viscosity @ 40°C		**150**
ISO Viscosity @ 100°C		**14.3**
Density @ 15°C	ASTM D4052	**0.891**
Pour Point, °C		**-15**
Flash Point (COC), °C		**230**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 10 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51524 Part 2 (HLP)
Parker	(Denison) HF-2, HF-1, HF-0
Eaton	Vickers I-286-S
Fives	(Cincinnati) P-68, P-69, P-70
Bosch Rexroth	RE 90 220
AFNOR	NF E 48-603 (HM)
ASTM	D6158 (HM)
SAE	MS 1004 (HM)
ISO	11158 (HM), 20763 vane pump test

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS HZ0523

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063