INDUSTRIAL OILS

SAROL 04 (DUSTROL).

A highly refined, solvent neutral paraffinic mineral oil supplied as a base fluid and dust suppressant.

PRODUCT RANGE
Industrial Specialities

APPLICATION

- Dust suppression
- Process and carrier oil applications
- Base fluid for customer blending

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Pale, clear liquid**
Density @ 15.6°C		**0.814-0.828**
Closed Flash Point, °C		**133**
Kinematic Viscosity @ 40°C, cSt		**3.5 – 4.5**
Boiling Point, °C		**>100**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS I00812

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063