TEXTILE LUBRICANTS

SAROL 100E.

SAROL 100E is a general purpose textile machine lubricant manufactured from a blend of solvent-refined mineral oils and non-ionic emulsifiers, used where scourability is required.

PRODUCT RANGE
Machine Lubricants

APPLICATION

- General purpose textile machinery lubricant where scourability is required

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour & Appearance		**Pale Amber liquid**
Density @ 15.6°C		**0.898 kg/m3**
Cloud Point, °C		**>70**
Kinematic Viscosity @ 40°C, cSt		**90 – 110**
Solubility in water		**Emulsifies readily**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS SOL100E

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063