METALWORKING FLUIDS

# SARSOL WHITEWATER CU.

SARSOL WHITEWATER CU is a high performance, emulsion soluble cutting fluid specially formulated for the machining of yellow metals, suitable for machining of all metals ferrous and non-ferrous, with increased passivation

PRODUCT RANGE
**Soluble Cutting Fluids**

## APPLICATION

- machining of all metals ferrous and non-ferrous
- brass
- bronze
- copper
- aluminium

**NOT RECOMMENDED**

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

## BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Appearance (Concentrate) | | **Amber liquid** |
| Appearance (Emulsion) | | **Milky** |
| pH (3% emulsion) | | **8.9 – 9.1** |
| IP 287 Breakpoint, % | | **4.0** |
| Mineral Oil Content | | **High** |
| Refractometer Conversion Factor | | **1.0** |
| Make Up Water Hardness, ppm | | **50 – 450** |
| Light Duty, % | | **5.0% – 6.0** |
| Medium Duty, % | | **7.0% – 8.0** |
| Heavy Duty, % | | **8.0% – 10.0** |

Typical values. They do not form a specification.

## PACK SIZES

25 L, 205 L, 1000 L IBC

**HEALTH AND SAFETY**

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IC0386

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063