TEXTILE LUBRICANTS

SARSTAT C.

SARSTAT C is an anti-static agent that can be employed at various stages of fibre/yarn processing and has proved to be very effective on most textile fibres including synthetic fibres such as acrylic and nylon.

PRODUCT RANGE

Anti-Static Agents

APPLICATION

- fibre/yarn processing
- gilling
- static dissipation on acrylic and nylon fibres
- spray application
- roller application

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear, water-white liquid**
Ionic Character		**Cationic**
Density		**1.0**
Solubility		**Mixes readily with water**
Biodegradability	OECD 301B	**Expected to be biodegradable**

Typical values. They do not form a specification.

PACK SIZES

25 Kilo Kegs, 200 Kilo Drums, 1000 Kilo IBC's

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS STATC

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063