METALWORKING FLUIDS

SARTEC 10.

SARTEC 10 is a low viscosity rust preventative and water displacement fluid, which leaves a thin protective film.

PRODUCT RANGE
Anti-Corrosion Products

0.811	64 °C	Amber
Specific Gravity @ 15.6	Flash point	Colour

APPLICATION

- Short term protection of metal components stored undercover
- water displacement

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Fluid Oil**
Colour	ASTM D1500	**Amber**
Specific Gravity @ 15.6°C		**0.811**
Flash Point, °C	ASTM D92	**64**
Indoor Protection		**3 Months**
Outdoor Protection Covered		**Not Recommended**
Outdoor Protection Uncovered		**Not Recommended**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IP0320

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063