METALWORKING FLUIDS

SARTEC 30.

SARTEC 30 is a medium viscosity rust preventative dewatering fluid which leaves a thin protective film, formulated with a blend of corrosion inhibitors and waxes in a hydrocarbon base.

PRODUCT RANGE
Anti-Corrosion Products

8.5 cSt	0.834	64 °C	Amber
Viscosity @ 40°C	Specific Gravity @ 15.6	Flash point	Colour

APPLICATION

- Agricultural machinery
- steel stocks
- protection of ferrous and non-ferrous metals stored undercover

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Fluid Oil**
Specific Gravity @ 15.6°C		**0.834**
Colour	ASTM D1500	**Amber**
Flash Point, °C	ASTM D92	**64**
Kinematic Viscosity @ 40°C, cSt		**8.5**
Indoor Protection		**6 Months**
Outdoor Protection Covered		**2-4 Months**
Outdoor Protection Uncovered		**Not Recommended**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IP0391

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063