INDUSTRIAL OILS

SARTHERM AO68.

A mineral heat transfer fluid on highly refined base stock for closed and low temperature open thermal systems.

PRODUCT RANGE
Heat Transfer Oils

66.5 cSt	222 °C	-33 °C
Viscosity @ 40°C	Flash point	Pour point

APPLICATION

- Closed-loop thermal fluid heating systems
- Process heating on textile stenters and dryers
- Jacketed vessels and calenders
- Low temperature open thermal systems

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity @ 40°C, cSt		66.5
Pour Point, °C		-33
Flashpoint (COC), °C		222

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IH0869

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063