INDUSTRIAL OILS

SARTHERM LT.

A low viscosity heat transfer fluid designed for systems that have to work cold as well as hot.

PRODUCT RANGE
Heat Transfer Oils

10.5 cSt	0.867	140 °C	-30 °C
Viscosity @ 40°C	Density @ 15	Flash point	Pour point

APPLICATION

- Combined heating and cooling circuits
- Jacketed reactors swinging over a wide range
- Systems that must circulate from cold start
- Low temperature process cooling

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Pale Liquid**
Pour point, °C		**-30**
Flash point (PMCC), °C		**140**
Kinematic Viscosity @ 40°C, cSt		**10.5**
Density @ 15°C	ASTM D4052	**0.867**
Auto ignition temperature, °C		**310**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IH0120

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063