OFF-HIGHWAY & AGRICULTURE

SARTRAC STOU 15W-30.

The value grade in the STOU range, built to an earlier but still widely specified performance level, API CE/SF and ACEA E2 rather than CG-4 and E3.

PRODUCT RANGE
Super Universal Tractor Oils

APPLICATION

- Older tractors specified to API CE/SF
- Contractors running mixed-age fleets
- Cost-sensitive general farm use
- Machines that gain nothing from a CG-4 oil

NOT RECOMMENDED

- × Hydraulic systems requiring a fire-resistant or biodegradable fluid
- × Engines with after-treatment where a low-SAPS engine oil is specified

BENEFITS

- Formulated for high-contamination working environments, dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 9 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	CE / SF, GL-4
ACEA	E2
Ford	M2C-159B
Massey Ferguson	M1135, M1139
Allison	C3
John Deere	J20A, J20B, J27
CAT	TO-2
ZF	TE-ML 06A

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Kinematic Viscosity @ 100°C, cSt		**12.5**
Specific Gravity @ 15.6°C		**0.890**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AT0035

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063