OFF-HIGHWAY & AGRICULTURE

SHIRE OIL.

A very light, highly refined, water-white oil used on shire horse feathers to improve condition and appearance.

PRODUCT RANGE
Agricultural Specialities

20.8 cSt	0.841	210 °C
Viscosity @ 40°C	Specific Gravity @ 15	Flash point

APPLICATION

- Conditioning shire and heavy horse feathers
- Showing and turnout preparation
- Stable and yard use

NOT RECOMMENDED

- × Hydraulic systems requiring a fire-resistant or biodegradable fluid
- × Engines with after-treatment where a low-SAPS engine oil is specified

BENEFITS

- Formulated for high-contamination working environments, dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear, water white liquid**
Kinematic Viscosity @ 40°C, cSt		**20.8**
Specific Gravity @ 15°C		**0.841**
Flashpoint °C (CC)		**210**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IO0586

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063