INDUSTRIAL OILS

SLIDEWAY OIL 46.

A machine tool slideway oil to DIN 51502 CGLP.

PRODUCT RANGE
Slideway Oils

46 cSt	6.5 cSt	0.878	210 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15	Flash point

APPLICATION

- Horizontal and vertical machine tool slideways
- Machines with combined slideway and hydraulic systems
- Grinders and lathes where chatter is a quality issue
- Carriages, guides and headstocks

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51502 CGLP
Cincinnati	Lamb (formerly Milacron) – P53 (ISO 32), P47 (ISO 68), P50 (ISO 220)

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Kinematic Viscosity @ 40°C (mm2/s)		**46**
Kinematic Viscosity @ 100°C (mm2/s)		**6.5**
Flash Point (COC), °C		**210**
Density @ 15°C	ASTM D4052	**0.878**
Pour Point, °C		**-33**
Copper Corrosion 3hr @ 100°C (ASTM D130)		**Class 1**
Rust Test – Synthetic Sea Water (ASTM D665)		**Pass**
Four Ball EP Test, Wear Scar, 20kg, 60 min. (IP239), mm		**0.25**
Timken OK Load (IP240)		**60lb**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IS0106

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063