METALWORKING FLUIDS

SPARK EROSION FLUID EDM.

Low viscosity fluid, formulated from virtually colourless, low odour base stocks, designed for electrical discharge machining operations.

PRODUCT RANGE
Spark Erosion Fluids

4.0 cSt	0.812	102 °C	Fluid
Viscosity @ 40°C	Specific Gravity @ 15.6	Flash point	Appearance

APPLICATION

- Spark erosion and wire erosion machining operations

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Fluid**
Colour	ASTM D1500	**Clear**
Specific Gravity @ 15.6°C		**0.812**
Kinematic Viscosity @ 40°C, cSt		**4.0**
Flash Point (PMCC), °C		**102**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IO0900

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063