METALWORKING FLUIDS

SPARK EROSION FLUID SYNTH EDM.

Low viscosity, high flash point odourless fluid giving excellent electrode service life with good flushing and fines settlement characteristics, pale in colour to allow good workpiece visibility.

PRODUCT RANGE
Spark Erosion Fluids

2.4 cSt	125 °C	–50 °C
Viscosity @ 40°C	Flash point	Pour point

APPLICATION

- Spark erosion and wire erosion machining including fine cutting roughing and shaping

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour	ASTM D1500	**Clear fluid**
Kinematic Viscosity @ 40°C, cSt		**2.4**
Flash Point, °C		**125**
Pour point, °C		**–50**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IO0907

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063