INDUSTRIAL OILS

SPINDLE OIL – ISO 15.

A very light, highly refined spindle oil for high-speed machine tool spindles.

PRODUCT RANGE
Spindle Oils

15 cSt	3.3 cSt	0.852	180 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15	Flash point

APPLICATION

- High-speed CNC milling and grinding spindles
- Oil-mist and oil-air spindle systems
- Horizontal, vertical, bed and turret type machining centres
- Low pressure hydraulic control circuits

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
ISO Viscosity @ 40°C		**15**
ISO Viscosity @ 100°C		**3.3**
Density @ 15°C	ASTM D4052	**0.852**
Pour Point, °C		**-26**
Flash Point (COC), °C		**180**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0615

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063