METALWORKING FLUIDS

STAR NEAT CUTTING OIL.

Formulated using hydro-cracked base stocks and utilises advanced additive technology to achieve a high flash point and increased performance.

PRODUCT RANGE
Neat Cutting Oils

25.2 cSt	0.857	215 °C
Viscosity @ 40°C	Specific Gravity @ 15	Flash point

APPLICATION

- Machining medium to high tensile steel
- Yellow metals
- Aluminium alloys and stainless steel
- High speed sliding head and multislide machines

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Kinematic Viscosity @ 40°C, cSt		**25.2**
Copper Corrosion Test		**1a**
Flashpoint, °C		**215**
Specific Gravity @ 15°C		**0.857**
Chlorine	ASTM D808	**No**
Sulphur		**Yes**
Ester		**Yes**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS MW0700

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063