INDUSTRIAL OILS

STEAM CYLINDER OIL 1000.

The heaviest compounded steam cylinder oil, at ISO 1000 with a 315 °C flash point.

PRODUCT RANGE
Industrial Specialities

APPLICATION

- Large and superheated steam engines
- High temperature cylinder lubrication
- Stationary engines needing maximum film strength

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour	ASTM D1500	**Dark amber fluid**
Kinematic Viscosity @ 40°C (ISO 3104), cSt		**900 – 1100**
Flash Point (ISO 2592), °C		**315**
Density @ 15°C (ASTM D1298) kg/l		**0.931**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IO0261

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063