AUTOMOTIVE

SUPER TWO STROKE.

High performance, semi-synthetic two-stroke oil engineered for modern two-stroke engines in scooters, motorcycles and equipment.

PRODUCT RANGE
Motorcycle Oils

6.95 cSt	0.872	140 °C	Red
Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point	Appearance

APPLICATION

- Two-stroke scooters and motorcycles
- Garden and grounds equipment
- Pre-mix and oil-injection systems

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable where the following specifications are required:

JASO	FD
API	TC
ISO-L-EGD	

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Type		**Semi-synthetic two-stroke oil**
Appearance	Visual	**Red**
Kinematic Viscosity @ 100°C, cSt		**6.95**
Specific Gravity @ 15.6°C		**0.872**
Flash Point, °C	ASTM D92	**140**

Typical values. They do not form a specification.

PACK SIZES

1 L, 4 L, 20 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0477

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063