TEXTILE LUBRICANTS

SUPERFLEX SPECIAL.

An aqueous emulsion of synthetic wax lubricants and polymers formulated for application as a warp wax or cold size to significantly improve weaving performance.

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- Warp wax/cold size for weaving; application rates range 0.6-1.6% for synthetic filament up to 8.0% max for linen and jute blends

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Milky white, opaque emulsion**
% Activity, %		**20 + 1**
Ionic Character		**Weakly Anionic**
pH		**6.0-8.0**
Viscosity (B4 Ford Cup), °C		**Typically 30 secs @ 20**
Anti-static Properties		**Excellent**
Solubility		**Easily miscible at all application temperatures**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS FG006

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063