METALWORKING FLUIDS

SUPERTEC 15.

SUPERTEC 15 is a medium to long term rust preventative which leaves a thin protective film, giving excellent indoor storage protection and also protection for components stored covered outdoors.

PRODUCT RANGE

Anti-Corrosion Products

APPLICATION

- Metal stocks
- Agricultural machinery

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Amber fluid**
Specific Gravity @ 15°C		**0.809**
Flash Point (COC), °C		**38**
Non-volatile residue, %		**17**
Film Thickness		**20 microns**
Indoor Protection		**6 Months**
Outdoor Protection Covered		**1 Month**
Outdoor Protection Uncovered		**Not Recommended**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IP0515

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063