METALWORKING FLUIDS

SUPERTEC 26 EXTRA.

SUPERTEC 26 EXTRA is a high quality rust preventative capable of offering excellent storage protection of over 30 months indoor and 24 months outdoor.

PRODUCT RANGE

Anti-Corrosion Products

APPLICATION

- Metal stocks
- Agricultural machinery
- High surface temperature components

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Amber/Brown fluid**
Specific Gravity @15°C		**0.894**
Flash Point (COC), °C		**>150**
Indoor Protection		**30 Months**
Outdoor Protection Covered		**24 Months**
Outdoor Protection Uncovered		**Not Recommended**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IP0545

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063