METALWORKING FLUIDS

SUPERTEC DW 941.

SUPERTEC DW 941 is a pale, low viscosity oil based, barium free, penetrating rust preventive containing a specially formulated additive package which inhibits corrosion on ferrous and aluminium alloy components.

PRODUCT RANGE
Anti-Corrosion Products

APPLICATION

- Precision machined components
- Cold rolled strip
- Component assembly aid
- Light to medium duty press lubricant for metal strip

NOT RECOMMENDED

- × Machining of magnesium, or of aluminium where a low-pH fluid is required
- × Use as a hydraulic or slideway oil, cross-contamination will shorten sump life

BENEFITS

- Extends tool life and improves surface finish across mixed materials
- Long sump life reduces fluid spend, disposal cost and machine downtime
- Formulated with operator health in mind, free from chlorine and formaldehyde donors
- Resists bacterial growth and the odours that come with a tired sump

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Film Type		**Light Oil/Grease**
Flash Point, °C	ASTM D92	**125**
Film Thickness		**1.5 microns**
Coverage		**650sqm/l**
Hot Salt Spray ASTM B117		**>16 – 24hrs**
Humidity DIN 50017KFW		**20 cycles**
Indoor Protection		**9 Months**
Outdoor Protection Covered		**3 Month**
Outdoor Protection Uncovered		**Not Recommended**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS IP0941

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063