AUTOMOTIVE

SYNGEAR MTF 94.

A premium quality, semi-synthetic gearbox fluid designed for higher output manual transmissions, offering enhanced friction characteristics for cold-weather shifting, thermal degradation/oxidation resistance and high vis

PRODUCT RANGE

Manual Transmission Fluids

64.5 cSt	10.3 cSt	0.874	>185 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Manual transmissions requiring MTF 94 specification
- Rover 25, 45, MGF models
- Certain Land Rover vehicles
- Honda vehicles
- BMW/MINI vehicles

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

SAE	75w80
API	GL-4
Rover/Land	Rover MTF 94
Honda	MTF94, MTF2
BMW	MTF LT-2

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Kinematic Viscosity @ 100°C, cSt		**10.3**
Kinematic Viscosity @ 40°C, cSt		**64.5**
Viscosity Index	ASTM D2270	**147**
Specific Gravity @ 15.6°C		**0.874**
Flash Point (COC), °C		**>185**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC (Other pack sizes and bulk deliveries up to 25,000 litres available on request)

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0768G

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063