AUTOMOTIVE

SYNGEAR PLUS 75W-90.

A full synthetic 75W-90 transmission and axle oil covering both API GL-4 and GL-5.

PRODUCT RANGE
Gear & Axle Oils

APPLICATION

- Extended-drain axles and gearboxes
- Fuel economy programmes on mixed fleets
- Applications specified 75W-90 synthetic
- Cold-start sensitive drivelines

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL-4 / GL-5

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Density @ 15.6°C		**0.860**
Viscosity @ 100°C, cSt		**14.3**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AG0618

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063