AUTOMOTIVE

SYNMAX 5W-40.

High-performance, full synthetic engine oil for use in both petrol and diesel engines, covering a wide spread of European OEM requirements.

PRODUCT RANGE
Passenger Car Engine Oils

14.9 cSt	225 °C	-40 °C
Viscosity @ 100°C	Flash point	Pour point

APPLICATION

- Mixed European car workshops
- High-output petrol and diesel
- Performance and Porsche A40 applications

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 5W-40**
Base Oil		**Full synthetic**
Density @ 15°C, g/cm³	ASTM D4052	**0.854**
Kinematic Viscosity @ 100°C, cSt		**14.9**
Viscosity Index	ASTM D2270	**168**
Flash Point, °C	ASTM D92	**225**
Pour Point, °C	ASTM D97	**-40**
TBN, mg KOH/g	ASTM D2896	**11.02**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

BENEFITS

- Synthetic base stocks give a wider operating temperature window than mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 12 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	SN/CF
ACEA	A3/B4
MB	229.1, 229.3, 229.5
Porsche	A40
Renault	RN 0700, RN 0710
Fiat	9.55535-Z2
PSA	B71 2296
GM	LL-A-025/LL-B-025
JASO	MA2

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0627

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063