AUTOMOTIVE

SYNMAX APOLLO 0W-20.

Full synthetic, fuel efficient petrol/diesel engine oil engineered for modern turbocharged direct injection engines, with enhanced detergency and anti-wear protection.

PRODUCT RANGE

Passenger Car Engine Oils

8.3 cSt	> 200 °C	-44 °C
Viscosity @ 100°C	Flash point	Pour point

APPLICATION

- BMW, Mercedes-Benz and Vauxhall/Opel passenger cars
- Hyundai/Kia, Toyota, Fiat, Alfa Romeo, Chrysler and Jeep
- Hybrid-electric variants specifying this grade

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 0W-20**
Base Oil		**Full synthetic**
Kinematic Viscosity @ 100°C, cSt		**8.3**
Density @ 15.6°C, g/cm³		**0.845**
TBN, mg KOH/g	ASTM D2896	**8.1**
Sulphated Ash, %	ASTM D874	**< 0.8**
Flash Point, °C	ASTM D92	**> 200**
Pour Point, °C	ASTM D97	**-44**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L (Other pack sizes and bulk deliveries up to 25,000 litres are available on request.)

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	C6, C5
API	SP, SP-R
CILSAC	GF-6A
BMW	LL-17FE+, LL-14FE+
MB	229.72, 229.71
Vauxhall/Opel	OV 040 1547-A20
Ford	M2C 947-B1, M2C 962-A1
JLR	ST
JLR.03.5006	
Chrysler	MS-12145
Fiat	9.55535-GSX

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08036

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063