AUTOMOTIVE

SYNMAX ECO-V 0W-20.

Full synthetic, fuel-efficient engine oil for modern turbocharged direct injection petrol engines, with LSPI protection.

PRODUCT RANGE
Passenger Car Engine Oils

8.2 cSt	> 200 °C	-48 °C	Green
Viscosity @ 100°C	Flash point	Pour point	Colour

APPLICATION

- VW Group engines specifying 508.00/509.00
- Porsche C20 applications
- Turbocharged GDI petrol engines

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 6 industry and OEM approvals, simplifying product consolidation

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 0W-20**
Base Oil		**Full synthetic**
Colour	ASTM D1500	**Green**
Kinematic Viscosity @ 100°C, cSt		**8.2**
Density @ 15.6°C, g/cm³		**0.847**
TBN, mg KOH/g	ASTM D2896	**8.3**
Flash Point, °C	ASTM D92	**> 200**
Pour Point, °C	ASTM D97	**-48**

Typical values. They do not form a specification.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	C5
API	SN Plus
VW	508.00, 509.00
Porsche	C20
Ford	M2C-956-A1

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08032

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063