AUTOMOTIVE

SYNMAX GENESIS 0W-30.

Full synthetic, fuel-efficient engine oil for modern petrol and diesel engines fitted with exhaust after-treatment systems.

PRODUCT RANGE
Passenger Car Engine Oils

9.6 cSt	> 200 °C	-42 °C
Viscosity @ 100°C	Flash point	Pour point

APPLICATION

- Ford diesel passenger cars and light commercial vehicles from 2014 requiring Ford M2C-950A
- Jaguar Land Rover Ingenium diesel engines requiring STJLR.03.5007

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	C2
Ford	M2C-950A
JLRSJLR.03.5007 (approved)	

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 0W-30**
Base Oil		**Full synthetic**
Kinematic Viscosity @ 100°C, cSt		**9.6**
Density @ 15.6°C, g/cm³		**0.840**
Pour Point, °C	ASTM D97	**-42**
Flash Point, °C	ASTM D92	**> 200**
TBN, mg KOH/g	ASTM D2896	**8.0**
Sulphated Ash, %	ASTM D874	**< 0.8**

Typical values. They do not form a specification.

PACK SIZES

Available in 0 pack sizes, ordered through our sales team rather than online (Other pack sizes and bulk deliveries up to 25,000 litres are available on request.)

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08015

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063