COMMERCIAL VEHICLES

SYNMAX OMEGA XFE 5W-30.

Full synthetic, fuel efficient, low SAPS heavy duty diesel engine oil formulated for modern Euro 6 engines with emission control technology.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

APPLICATION

- Latest-generation Euro 6 heavy duty diesel
- Mercedes-Benz FE models to MB 228.61
- Fleets running low-sulphur diesel under severe duty

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 5W-30**
Base Oil		**Full synthetic**
Density @ 15°C, g/cm³	ASTM D4052	**0.858**
Kinematic Viscosity @ 100°C, cSt		**12.2**
Viscosity Index	ASTM D2270	**165**
NOACK, % wt		**11**
Phosphorus, % wt		**> 0.12**
Sulphated Ash, % wt	ASTM D874	**< 1.0**
TBN, mg KOH/g	ASTM D2896	**12.8**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	FA-4
Volvo	VDS-5
Renault	RLD-5
Mack	EOS-5
Daimler Truck	DTFR 15C130 (MB 228.61)
Cummins	CES 20087
JASO	DH-2
Detroit Diesel	93K223

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08024

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063