COMMERCIAL VEHICLES

SYNMAX ORION FE 5W-30.

Full synthetic, fuel efficient, low SAPS heavy duty diesel engine oil for modern powerplants with DPF or SCR after-treatment.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

APPLICATION

- Euro 6 engines with advanced emissions treatment
- Mixed fleets on extended drain
- Operation on low-sulphur diesel (50 ppm or below)

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

COMMERCIAL VEHICLES · CONTINUED

SYNMAX ORION FE 5W-30.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	E4/E6/E7/E8/E9/E11
API	CK-4
Volvo	VDS-4.5
Renault	RLD-3
Mack	EO-S 4.5
Scania	LDF-4
MB	228.51/228.52
MAN	M3271-1/M3575/M3677/M3775/M3777
Caterpillar	ECF-3
Cummins	CES 20086/20081
Deutz	DQC IV-18 LAM
TU	Type 2.1/3.1
JASO	DH-2
DAF	Euro 6
IVECO	18-1804

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 5W-30**
Base Oil		**Full synthetic**
Density @ 15°C, g/cm³	ASTM D4052	**0.848**
Kinematic Viscosity @ 100°C, cSt		**11.9**
Viscosity Index	ASTM D2270	**168**
Sulphated Ash, % wt	ASTM D874	**< 1.0**
TBN, mg KOH/g	ASTM D2896	**12.8**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08014

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063