COMMERCIAL VEHICLES

SYNMAX PERFORMANCE PLUS E4 10W-40.

High performance, synthetic-based heavy duty diesel engine oil for Euro 4, Euro 5 and Euro 6 engines requiring an ACEA E4 specification oil.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

93.3 cSt	14.1 cSt	-34 °C
Viscosity @ 40°C	Viscosity @ 100°C	Pour point

APPLICATION

- Fleets specifying ACEA E4
- Longest permitted drain intervals
- Euro 4 to Euro 6 engines

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 10W-40**
Base Oil		**Synthetic based**
Kinematic Viscosity @ 40°C, cSt		**93.3**
Kinematic Viscosity @ 100°C, cSt		**14.1**
Viscosity Index	ASTM D2270	**155**
Density @ 15°C, g/cm³	ASTM D4052	**0.863**
Pour Point, °C	ASTM D97	**-34**
Sulphated Ash, %	ASTM D874	**< 1.0**
TBN, mg KOH/g	ASTM D2896	**> 14**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	E4, E7
API	CF-4
MAN	M3277 (approval pending)
Volvo	VDS-3
Renault	RLD-2
Mack	E-ON
MTU	Type 3
Caterpillar	ECF-1a
Deutz	DQC III-10
DAF	Extended Drain
Daimler Truck	DTFR 15B120

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08033

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063