COMMERCIAL VEHICLES

SYNMAX PERFORMANCE PLUS E6 10W-40.

High performance, full synthetic, low SAPS heavy duty diesel engine oil for Euro 4 to Euro 6 engines with emission control systems.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

98.38 cSt	14.79 cSt	180 °C	-42 °C
Viscosity @ 40°C	Viscosity @ 100°C	Flash point	Pour point

APPLICATION

- Euro 4 to Euro 6 with DPF and SCR
- Low-SAPS fleet consolidation
- Municipal and refuse vehicles

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 10W-40**
Base Oil		**Full synthetic**
Density @ 15°C, g/cm³	ASTM D4052	**0.855**
Kinematic Viscosity @ 40°C, cSt		**98.38**
Kinematic Viscosity @ 100°C, cSt		**14.79**
Viscosity Index	ASTM D2270	**157**
Flash Point, °C	ASTM D92	**180**
Pour Point, °C	ASTM D97	**-42**
Sulphated Ash, %	ASTM D874	**< 1.0**
TBN, mg KOH/g	ASTM D2896	**9.0**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	E6, E7
API	CI-4
MB	228.51
Volvo	VDS-3
Mack	EO-N
Renault	RLD-2
MAN	3477
MTU	3.1
Deutz	DQC IV-10 LAD
AFD	
Daimler Truck	DTFR 15B120

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE0653

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063