COMMERCIAL VEHICLES

SYNMAX SCORPIO 10W-40.

High performance, full synthetic, low SAPS heavy duty diesel engine oil for Euro 4, 5 and 6 engines with emissions treatment systems.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

83.1 cSt	13.1 cSt	189 °C	-40 °C
Viscosity @ 40°C	Viscosity @ 100°C	Flash point	Pour point

APPLICATION

- Euro 4 to Euro 6 with after-treatment
- Mixed fleets on a single low-SAPS oil
- Extended drain programmes

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

COMMERCIAL VEHICLES · CONTINUED

SYNMAX SCORPIO 10W-40.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	E6/E7/E8/E9/E11
API	CK-4
MB	228.51
Volvo	VDS-4.5
Renault	RLD-3
Mack	EO-S 4.5
Caterpillar	ECF-3
Cummins	CES 20086
MAN	M3477/M3271-1
Scania	LAMTU 3.1
Deutz	DQC IV-10 LA
JASO	DH-2
DAF	Euro 6
IVECO	TLS 18-1804 E9

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 10W-40**
Base Oil		**Full synthetic**
Density @ 15°C, g/cm³	ASTM D4052	**0.859**
Kinematic Viscosity @ 40°C, cSt		**83.1**
Kinematic Viscosity @ 100°C, cSt		**13.1**
Viscosity Index	ASTM D2270	**159**
Flash Point, °C	ASTM D92	**189**
Pour Point, °C	ASTM D97	**-40**
Sulphated Ash, %	ASTM D874	**< 1.0**
TBN, mg KOH/g	ASTM D2896	**10.5**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08016

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063