AUTOMOTIVE

SYNMAX SPECTRUM 5W-30.

Full synthetic mid-SAPS engine oil for contemporary petrol and diesel powerplants fitted with diesel particulate filters and three-way catalysts.

PRODUCT RANGE
Passenger Car Engine Oils

APPLICATION

- Passenger cars and light commercials requiring ACEA C2 or C3
- Vehicles with DPF and three-way catalyst
- Euro IV and Euro V emission standards

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 5W-30**
Base Oil		**Full synthetic**
Kinematic Viscosity @ 40°C, cSt		**68.9**
Kinematic Viscosity @ 100°C, cSt		**11.6**
Viscosity Index	ASTM D2270	**164**
TBN, mg KOH/g	ASTM D2896	**7.5**
Density @ 15.6°C, g/cm³		**0.847**
Sulphated Ash, %	ASTM D874	**≤ 0.8**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	C2, C3
API	SN, SM
MB	229.31
GM	dexos2™

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08018

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063