AUTOMOTIVE

SYNMAX STELLAR 5W-30.

Full synthetic mid-SAPS engine oil formulated with advanced performance technology for the latest designs of petrol and diesel engine.

PRODUCT RANGE
Passenger Car Engine Oils

APPLICATION

- Stellantis group petrol and diesel engines
- Mercedes-Benz long-life servicing
- Mixed European car fleets

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 5W-30**
Base Oil		**Full synthetic**
Specific Gravity @ 15.6°C		**0.846**
Kinematic Viscosity @ 100°C, cSt		**11.8**
Viscosity Index	ASTM D2270	**183**
Sulphated Ash	ASTM D874	**0.8 % max**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	C2, C3
API	SN, SM, SL
GM	dexos2™
MB	229.52, 229.51, 229.31
PSA	B71 2297, B71 2290
Stellantis	FPW 9.55535.03

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08038

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063