COMMERCIAL VEHICLES

SYNMAX TRITON XFE 5W-20.

A full synthetic, low SAPS 5W-20 heavy duty diesel oil for the very newest Scania and MAN engines, approved to Scania LDF-5 and MAN M3977.

PRODUCT RANGE

Heavy Duty Diesel Engine Oils

0.856	-42 °C	Green
Density @ 15	Pour point	Colour

APPLICATION

- Latest Scania engines on LDF-5
- MAN M3977 applications
- Fuel economy programmes on modern fleets
- Long-haul operations with aftertreatment

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable where the following specifications are required:

SCANIA	LDF-5
MAN	M3977

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Colour	ASTM D1500	**Green**
KV @ 100°C, cSt		**8.4**
KV @ 40°C, cSt		**49.2**
Viscosity Index	ASTM D2270	**146**
Density @ 15°C	ASTM D4052	**0.856**
Pour Point, °C	ASTM D97	**-42**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08033

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063