AUTOMOTIVE

SYNMAX ULTRA ECO 5W-20.

Premium full synthetic, fuel-efficient engine oil formulated for Ford EcoBoost engines.

PRODUCT RANGE
Passenger Car Engine Oils

APPLICATION

- Ford EcoBoost petrol engines
- Jaguar and Land Rover 5W-20 applications

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 5W-20**
Base Oil		**Full synthetic**
Kinematic Viscosity @ 100°C, cSt		**8.0**
TBN, mg KOH/g	ASTM D2896	**8.2**
Viscosity Index	ASTM D2270	**162**
Sulphated Ash, %	ASTM D874	**< 0.8**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

BENEFITS

- Synthetic base stocks give a wider operating temperature window than mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over full drain interval
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across full service interval

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	C5
API	SN/CF
Ford	M2C-948B (EcoBoost), M2C-913B/913C, M2C-925A/925B
JLR	ST
JLR.03.5004	

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08011

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063