AUTOMOTIVE

SYNMAX ULTRA LONGLIFE C4 5W-30.

Full synthetic very low SAPS engine oil for the latest technology in both petrol and diesel engines.

PRODUCT RANGE
Passenger Car Engine Oils

APPLICATION

- Renault diesel engines with DPF
- Very low SAPS after-treatment systems

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 4 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	C4
Renault	RN 0720
MB	226.51, 229.51

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 5W-30**
Base Oil		**Full synthetic**
Kinematic Viscosity @ 100°C, cSt		**11.9**
Density @ 15°C, g/cm³	ASTM D4052	**0.8445**
Sulphated Ash, %	ASTM D874	**≤ 0.5**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE08009

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063