AUTOMOTIVE

SYNMAX VEGA 0W-20.

Premium full synthetic, fuel-efficient engine oil developed for Volvo Drive-E engines and vehicles requiring ACEA C5.

PRODUCT RANGE
Passenger Car Engine Oils

8.3 cSt	> 200 °C	-40 °C
Viscosity @ 100°C	Flash point	Pour point

APPLICATION

- Volvo Drive-E VEP petrol engines
- Volvo VED diesel engines

NOT RECOMMENDED

- × Engines specifying a viscosity grade or OEM approval not listed above
- × Two-stroke engines, unless a dedicated two-stroke product is specified

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Viscosity Grade	SAE J300	**SAE 0W-20**
Base Oil		**Full synthetic**
Kinematic Viscosity @ 100°C, cSt		**8.3**
Density @ 15.6°C, g/cm³		**0.844**
TBN, mg KOH/g	ASTM D2896	**8.1**
Viscosity Index	ASTM D2270	**186**
Sulphated Ash, %	ASTM D874	**< 0.8**
Flash Point, °C	ASTM D92	**> 200**
Pour Point, °C	ASTM D97	**-40**

Typical values. They do not form a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ACEA	C5
Volvo	VCC RBS0-2AE (approved)

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AE8019

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063