INDUSTRIAL OILS

SYNTH PAO COMPRESSOR OIL 32.

The lightest grade in the full synthetic compressor range, and the one to reach for when cold starting is the constraint.

PRODUCT RANGE
Compressor Oils

32 cSt	0.84	210 °C	-55 °C
Viscosity @ 40°C	Relative Density @ 15	Flash point	Pour point

APPLICATION

- Cold-start critical compressor installations
- Light-duty rotary screw machines
- Outdoor and unheated compressor housings

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable where the following specifications are required:

DIN	51506 (VDL)
ISO	DP 6521 (DAG)

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Relative Density @ 15°C		**0.84**
Pour Point, °C		**-55**
Flash Point, COC °C min		**210**
Viscosity, cSt @ 40°C		**32**
Rust (ASTM D 665 A)		**Pass**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS CLSYN0032

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063