GREASES

# SYNTHETIC HIGH TEMP RED 007 GREASE.

The semi-fluid member of the synthetic high temperature family: an NLGI 00 lithium complex grease on a 460 cSt synthetic blend with PTFE.

PRODUCT RANGE

**High Temperature Greases**

## APPLICATION

- Centralised lubrication of hot bearings
- Semi-fluid feed to oven and dryer bearings
- Hot gearboxes designed for a slumping grease

### NOT RECOMMENDED

- × Applications requiring an NSF H1 food-grade grease
- × Mixing with greases of a different thickener type without purging the bearing first
- × Continuous service above the stated upper temperature limit

## BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable, will not soften and leak in service

## TYPICAL PROPERTIES

| PROPERTY | METHOD | TYPICAL |
|---|---|---|
| Appearance | Visual | **Smooth Red grease** |
| Thickener | | **Lithium Complex** |
| NLGI classification | | **00** |
| Base oil | | **A blend of synthetic oils** |
| Base oil Viscosity, cSt | | **460** |
| Solid lubricant | | **PTFE** |
| Dropping point (ASTM D2265), °C | | **>230** |
| Dynamic corrosion resistance (EMCOR) (IP 220) | | **0:0** |
| Weld Load (Shell 4 Ball IP 239/ASTM D2596) | | **355kgs** |
| Load Wear Index | | **68kg** |
| Corrosion (ASTM D130) | | **1b** |
| dN factor | | **750,000** |
| Operating temperature range, °C | | **-50°C to 170°C with short periods up to 200** |

Typical values. They do not form a specification.

## PACK SIZES

12.5 kg, 50 kg, 180 kg

### HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS GR0007R

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063