TEXTILE LUBRICANTS

SYNTHOLENE PLUS 5.

SYNTHOLENE PLUS 5 is a blend of polyoxyalkylene derivatives with an addition of non-ionic surfactants, used as a processing aid for the lubrication of fibres through carding and spinning.

PRODUCT RANGE
Fibre & Yarn Lubricants

APPLICATION

- Lubrication of fibres through carding and spinning (2-5% on weight of fibre)
- Water application (5-10% on weight of fibre)

NOT RECOMMENDED

- × Any application requiring food-grade or NSF H1 registration
- × Bearings and gearboxes requiring a fully formulated industrial lubricant

BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance, °C	Visual	**Clear Liquid @ 20**
Colour	ASTM D1500	**Colourless**
Odour		**Mild**
Specific Gravity @ 15.6°C		**1.15**
pH		**5-7**
Pour Point, °C	ASTM D97	**Less Than 5**
Solubility		**Fully Soluble**

Typical values. They do not form a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS SNTH705

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063