INDUSTRIAL OILS

SYNVAC VACUUM PUMP OIL 100.

A full synthetic PAO vacuum pump oil with a non-toxic formulation.

PRODUCT RANGE
Vacuum & Airline Oils

100 cSt	14.0 cSt	266 °C
Viscosity @ 40°C	Viscosity @ 100°C	Flash point

APPLICATION

- Continuously running vacuum pumps
- Food and pharmaceutical packaging plant
- Hot-running pumps where mineral oil oxidises too fast
- Extended-drain vacuum service

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Appearance	Visual	**Clear fluid**
Base fluid		**PolyAlphaOlefin**
Viscosity @40°C – typical, cSt		**100**
Viscosity @100°C – typical, cSt		**14.0**
Temperature range, °C		**-40°C – +150**
Flashpoint, °C		**266**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS SYNVAC100

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063