COMMERCIAL VEHICLES

TECHGEAR 75W-90.

The top of the driveline range: a full synthetic 75W-90 carrying an OEM approval list few gear oils reach, SAE J2360, Scania STO 1:0 and 1:0 G, Mack GO-J Plus, MAN 341 M3/Z2 and 342 S1, Mercedes-Benz 235.80, Volvo 97312

PRODUCT RANGE
Transmission & Axle Oils

98.6 cSt	15.2 cSt	0.871	220 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6	Flash point

APPLICATION

- Modern truck and bus drive axles
- Extended drain fleet programmes
- Warranty-sensitive OEM applications
- Fuel economy driveline specifications

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 16 industry and OEM approvals, simplifying product consolidation

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063

COMMERCIAL VEHICLES · CONTINUED

TECHGEAR 75W-90.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL-4/5, MT-1
MIL-PRF	2105E
SAE	J-2360
FORD	M2C-200C
SCANIA	STO 1:0, STO 1:0 G
MACK	GO-J Plus
Arvin	Meritor Axles
DAF	requirement
MAN	341 Type M3/Z2, 342 Type S1
MB	235.80
NATO	O-226
VOLVO	97312/97315
ZF	TE-ML 02B/05B/07A/12B/16F/17B/19C/21B

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Density @ 15.6°C		**0.871**
Viscosity @ 100°C, cSt		**15.2**
Viscosity @ 40°C, cSt		**98.6**
Flash Point, °C		**220**
Pour Point, °C		**-24**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AG0631

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063