COMMERCIAL VEHICLES

TECHGEAR S 75W80.

A fully synthetic, fuel-efficient gear oil for commercial vehicle drivelines, formulated for rapid circulation from cold start and extended service life under heavy-duty operating conditions.

PRODUCT RANGE
Transmission & Axle Oils

56.7 cSt	9.61 cSt	0.853	192 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6	Flash point

APPLICATION

- Axles, transfer cases and final drives on late-model trucks and buses
- Non-synchronised manual transmissions requiring API MT-1

NOT RECOMMENDED

- × Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system
- × Applications calling for an API CJ-4 or older specification without checking backward compatibility

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems, EGR, SCR and DPF, from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable where the following specifications are required:

API	GL-4/5, MT-1
MIL-PRF	2105E
SAE	J-2360
Arvin	Meritor 076
SDAF	requirement
MAN	342 Type S1

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Density @ 15.6°C		**0.853**
Viscosity @ 40°C, cSt		**56.7**
Viscosity @ 100°C, cSt	ASTM D445	**9.61**
Flash Point, °C	ASTM D92	**192**
Pour Point, °C	ASTM D97	**-42**

Typical values. They do not form a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS AG0633

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063