INDUSTRIAL OILS

TITANIUM V COMPRESSOR OIL 68.

A semi-synthetic compressor oil that sits deliberately between the mineral and full synthetic ranges.

PRODUCT RANGE
Compressor Oils

68 cSt	0.88	210 °C	-30 °C
Viscosity @ 40°C	Relative Density @ 15°C / 4	Flash point	Pour point

APPLICATION

- Workshop and light industrial compressors
- 4,000 hour extended service intervals
- Operators stepping up from a mineral fill without paying for full synthetic

NOT RECOMMENDED

- × Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid
- × Food production areas where an NSF H1 registered lubricant is required
- × Applications above the stated maximum operating temperature

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable where the following specifications are required:

ISO	6743-3:2003 L-DAH specification, DP 6521 (DAG)
DIN	51506 (VDL)

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Relative Density @ 15°C / 4°C		**0.88**
Pour Point, °C		**-30**
Flash Point, COC °C min		**210**
Viscosity, cSt @ 40°C		**68**
Rust (ASTM D 665 A)		**Pass**

Typical values. They do not form a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS CLR0068

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063