MASTER FLUID SOLUTIONS

TRIM E950.

High-performance, aerospace-approved metalworking fluid compliant with Rolls-Royce CSS129 and CSS131, developed for demanding precision machining.

PRODUCT RANGE
Soluble Cutting Fluids

APPLICATION

- Aerospace and defence precision machining
- Titanium, nickel-based superalloys and aluminium alloys
- Sites needing extended sump life and fewer cleanouts

TYPICAL PROPERTIES

PROPERTY	METHOD	TYPICAL
Type		**Soluble oil emulsion**
Typical Dilution, %		**5 – 10**
Lubricity		**High**
Chlorine	ASTM D808	**None**

Typical values. They do not form a specification.

PERFORMANCE PROFILE

Suitable where the following specifications are required:

Rolls-Royce	CSS129, CSS131
Aerospace	approved

PACK SIZES

205 L, 1000 L IBC, Bulk. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH AND SAFETY

Read the safety data sheet before use. It covers handling, health and disposal and should be passed on to anyone who works with this product. Read all precautions on container labels.

SDS on request

SAR Lubricants (Squire A. Radcliffe & Sons Ltd) · Gill Bridge Works, Lowlands Road, Mirfield, WF14 8LU
+44 (0)1924 494371 · enquiries@sarlubricants.co.uk · sarlubricants.co.uk · Registered in England 05866783 · VAT 889171063